


Eibach[®] **THE WILL** **SPRINGS** **TO WIN**



Eibach Valve Springs



EVS-Pro

- Race-Proven-Motorsport Quality
- Maximum Lift for Maximum Performance and Durability
- Increased Seat Pressure for Optimum Performance
- Higher Natural Frequency for High RPM Capability
- Dual Chamfering for Lower Wear on Seats and Retainers
- In-House SpinTron and Bosch Dynamic Testing
- Automated Production for Consistent Quality
- Easy Installation with Stock Retainers-
No Machining Required

Now, using the very same Eibach technology used in IRL, Circle Track, Grand Am and Speed World Challenge, you can get your engine performing at its very best. Eibach **EVS-Pro** valve springs are precision engineered and made from the highest quality material-eliminating the need for a dampening inner spring.

The result: less weight and more performance.



Contents

Page

Competition Push Rod

3

Domestic

4

Import

5- 6

Motorcycle

6

EVS Specifications

7

Competition Push Rod Engine Applications



Make/Model Part Number	Type	O.D	I.D	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
Roller Lifter							
30003.02 (Each)	Dual Spring	1.50"	0.78"	229 lbs @ 1.90"	547 lbs @ 1.25"	0.65"	1.12"
30003.216 (Set of 16)							
30013.02 (Each)	Dual Spring	1.57"	0.825"	187 lbs @ 2.05"	546 lbs @ 1.40"	0.65"	1.25"
30013.216 (Set of 16)							
30004.02 (Each)	Dual Spring	1.58"	0.84"	243 lbs @ 1.95"	627 lbs @ 1.20"	0.75"	1.08"
30004.216 (Set of 16)							
30010.02 (Each)	Dual Spring	1.59"	0.84"	220 lbs @ 2.05"	712 lb @ 1.25"	0.80"	1.17"
30010.216 (Set of 16)							
35003.02 (Each)	Dual Spring	1.62" / 1.53"	0.83" / 0.74"	246 lbs @ 2.12"	714 lbs @ 1.33"	0.75"	1.15"
35003.216 (Set of 16)	Beehive						
30005.02 (Each)	Dual Spring	1.625"	0.85"	255 lbs @ 2.00"	691 lbs @ 1.25"	0.75"	1.13"
30005.216 (Set of 16)							
30012.02 (Each)	Dual Spring	1.625"	0.84"	270 lbs @ 2.00"	760 lb @ 1.25"	0.75"	1.16"
30012.216 (Set of 16)							
Flat Tappet							
30008.02 (Each)	Dual Spring	1.52"	0.80"	190 lbs @ 2.05"	584 lbs @ 1.25"	0.80"	1.17"
30008.216 (Set of 16)							
30001.02 (Each)	Dual Spring	1.57"	0.84"	203 lbs @ 2.05"	579 lbs @ 1.30"	0.75"	1.07"
30001.216 (Set of 16)							
Circle Track Restrictor Plate							
30007.01 (Each)	Single Spring	1.54"	1.12"	145 lbs @ 1.90"	330 lbs @ 1.35"	0.55"	1.24"
30007.116 (Set of 16)							
Drag Racing							
30020.02 (Each)	Dual Spring	1.66"	0.88"	305 lbs @ 2.15"	822 lbs @ 1.30"	0.85"	1.16"
30020.216 (Set of 16)							
30021.03 (Each)	Triple Spring	1.66"	0.63"	367 lbs @ 2.07"	967 lbs @ 1.27"	0.80"	1.19"
30021.316 (Set of 16)							



Domestic Applications (complete engine sets)

	Make/Model Part Number	Type	O.D	I.D	Seat Pressure	Open Pressure	Max. Lift	Coil Bind	
	Chevrolet Camaro / Corvette LS1 / LS6 V8								
	25408.116 (Set of 16)	Conical Spring	1.25"	0.89"	135 lbs @ 1.80"	288 lbs @ 1.20"	0.60"	1.11"	
	25410.116 (Set of 16) High load	Conical Spring	1.27"	0.88"	166 lbs @ 1.80"	389 lbs @ 1.25"	0.55"	1.18"	
	Chevrolet 262 - 400 V8								
	20415.116 (Set of 16)	Single Spring	1.23"	0.875"	92 lbs @ 1.70"	213 lbs @ 1.25"	0.45"	1.08"	
	Chevrolet 396/402/427/454 V8								
	20422.116 (Set of 16)	Single Spring	1.50"	1.09"	135 lbs @ 1.88"	287 lbs @ 1.35"	0.53"	1.24"	
	Chrysler 318 / 340 / 360 V8								
	20425.116 (Set of 16)	Single Spring	1.41"	1.02"	103 lbs @ 1.65"	241 lbs @ 1.20"	0.45"	1.07"	
	Chrysler 383 / 400 / 413 / 440 V8								
	20427.116 (Set of 16)	Single Spring	1.38"	1.02"	126 lbs @ 1.86"	210 lbs @ 1.40"	0.46"	1.08"	
	Ford Mustang / F- Series 4.6 L V8								
	25409.116 (Set of 16)	Conical Spring	1.04"	0.74"	84 lbs @ 1.57"	202 lbs @ 1.02"	0.55"	0.95"	
	Ford Mustang 4.6 / 5.4 32V V8								
	25414.132 (Set of 32)	Conical Spring	1.06"	0.75"	76 lbs @ 1.42"	223 lbs @ 0.95"	0.47"	0.82"	
	Ford 289 - 302 V8 63'-81'								
	20420.116 (Set of 16)	Single Spring	1.36"	1.00"	100 lbs @ 1.70"	209 lbs @ 1.20"	0.50"	0.97"	
	Pontiac Firebird / GTO LS1 / LS6								
	25408.116 (Set of 16)	Conical Spring	1.25"	0.89"	135 lbs @ 1.80"	288 lbs @ 1.20"	0.60"	1.11"	
	25410.116 (Set of 16) High Load	Conical Spring	1.27"	0.88"	166 lbs @ 1.80"	389 lbs @ 1.25"	0.55"	1.18"	

Import Applications (complete engine sets)



Make/Model Part Number	Type	O.D	I.D	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
Acura RSX / TSX K20 20411.216 (Set of 16)	Dual Spring	29.4 mm	16.9 mm	82 lbs @ 40.5 mm	238 lbs @ 27 mm	13.5 mm	25.3 mm
Acura NSX C30 20402.224 (Set of 24)	Dual Spring	29.3 mm	16.8 mm	80 lbs @ 36.4 mm	226 lbs @ 23.4 mm	13 mm	21.9 mm
Acura Integra B18 20401.216 (Set of 16)	Dual Spring	29.3 mm	16.8 mm	78 lbs @ 33.4 mm	212 lbs @ 21.4 mm	12 mm	18.8 mm
BMW E46 25435.116 (Set of 16)	Single Spring	30.05 mm	16 mm	79 lbs @ 37 mm	168 lbs @ 26.5 mm	10.5 mm	24.8 mm
BMW Mini 1.6 20463.116 (Set of 16)	Single Spring	26 mm	17.6 mm	80 lbs @ 43 mm	212 lbs @ 33 mm	11 mm	30.7 mm
Honda Civic Type R / Civic SI / B18 20401.216 (Set of 16)	Dual Spring	29.3 mm	16.8 mm	78 lbs @ 33.4 mm	212 lbs @ 21.4 mm	12 mm	18.8 mm
Honda Civic Type R / Civic SI / S2000 K20 / F20 20411.216 (Set of 16)	Dual Spring	29.4 mm	16.9 mm	82 lbs @ 40.5 mm	238 lbs @ 27 mm	13.5 mm	25.3 mm
Honda Prelude H22 20402.224 (Set of 24)	Dual Spring	29.3 mm	16.8 mm	80 lbs @ 36.4 mm	226 lbs @ 23.4 mm	13 mm	21.9 mm
Infiniti G35 3.5L 20452.124 (Set of 24)	Single Spring	24.8 mm	17.6 mm	65 lbs @ 38 mm	175 lbs @ 24.5 mm	13.5 mm	22.9 mm
Mazda Miata 1.8L 20410.116 (Set of 16) 20432.216* (Set of 16) *Spec Miata Race Spring, use Mazda retainer B6N7-12-123C B6N7-12-113	Single Spring Dual Spring	25.7 mm 26.6 mm	18.1 mm 14.2 mm	66 lbs @ 39 mm 75 lbs @ 35.8 mm	200 lbs @ 27 mm 210 lbs @ 24.1 mm	12 mm 11.7 mm	24.2 mm 22.1 mm
Mazda 3 / 6 2.0L / 2.3L 16V 25407.116 (Set of 16)	Conical Spring	24.8 mm	18 mm	47 lbs @ 35 mm	140 lbs @ 23.5 mm	11.5 mm	21.6 mm
Mitsubishi EVO VIII 25430.116 (Set of 16)	Conical Spring	26 mm	19.1 mm	85 lbs @ 38.1 mm	202 lbs @ 26.1 mm	12 mm	24.3 mm
Nissan 350Z 3.5L 20452.124 (Set of 24)	Single Spring	24.8 mm	17.6 mm	65 lbs @ 38 mm	175 lbs @ 24.5 mm	13.5 mm	22.9 mm
Nissan SR20DET 20466.116 (Set of 16)	Single Spring	29.2 mm	21 mm	82 lbs @ 39 mm	216 lbs @ 27.5 mm	11.5 mm	25.4 mm



Import Applications (complete engine sets) con't

Part Number	Type	O.D	I.D	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
Nissan RB26 20445.116 (Set of 16)	Single Spring	27 mm	19 mm	81 lbs @ 41.9 mm	211 lbs @ 29.9 mm	12 mm	28.4 mm
Porsche 911 Air Cooled 20701.212 (Set of 12) 20444.212 (Set of 12)	Dual Spring High Lift Spring	31.6 mm 31.75 mm	17.6 mm 17.3 mm	55 lbs @ 36.5 mm 90 lbs @ 36 mm	183 lbs @ 25.5 mm 277 lbs @ 23.3 mm	11 mm 12.7 mm	20.5 mm 20.7 mm
Porsche 996 GT3 / Turbo 20453.224 (Set of 24)	Double Spring	29.6 mm	17 mm	70 lbs @ 32.5 mm	225 lbs @ 18.5 mm	14 mm	16.8 mm
Subaru Impreza WRX / Sti 20457.116 (Set of 16)	Single Spring	26.7 mm	19.1 mm	62 lbs @ 36 mm	175 lbs @ 25 mm	11 mm	23.2 mm
Toyota 1ZZ 20409.116 (Set of 16)	Single Spring	22.2 mm	16.2 mm	39 lbs @ 33.4 mm	97 lbs @ 22.4 mm	11 mm	20.6 mm
Toyota 2ZZ 20407.116 (Set of 16)	Single Spring	22.5 mm	15.7 mm	48 lbs @ 39.4 mm	147 lbs @ 26.9 mm	12.5 mm	25 mm
VW Golf / Jetta / Passat 2.0L 8V 20406.208 (Set of 8)	Dual Spring	30.2 mm	17.9 mm	74 lbs @ 31.75 mm	189 lbs @ 20.25 mm	11.5 mm	16.1 mm
VW Golf / Jetta / Passat VR6 20406.212 (Set of 12)	Dual Spring	30.2 mm	17.9 mm	74 lbs @ 31.75 mm	189 lbs @ 20.25 mm	11.5 mm	16.1 mm

Motorcycle Applications (complete engine sets)

Part Number	Type	O.D	I.D	Seat Pressure	Open Pressure	Max. Lift	Coil Bind
Harley Davidson Evolution 1450cc 25413.204 (Set of 4) Retainer kit included	Dual Spring	1.38"	0.71"	133 lbs @ 1.78"	345 lbs @ 1.28"	0.50"	0.96"
Harley Davidson Evolution 1540cc 25412.204 (Set of 4) Retainer kit included	Dual Spring	1.38"	0.71"	149 lbs @ 1.78"	385 lbs @ 1.23"	0.55"	0.96"
Harley Davidson Panhead/Shovel 20433.204 (Set of 4) 20434.204 (Set of 4)	Dual Spring Dual Spring	1.65" 1.65"	0.87" 0.87"	131 lbs @ 1.50" 181 lbs @ 1.50"		0.53" 0.53"	0.88" 0.88"
Harley Davidson WL 20435.104 (Set of 4)	Single Spring	0.98"	0.66"	92 lbs @ 1.97"		0.50"	1.33"
Yamaha YZ250F / R1 20456.102 (Set of 2) 20458.102 (Set of 2)	Intake Spring Exhaust Spring	16.4 mm 19 mm	11.4 mm 11.4 mm	33 lbs @ 28 mm 40 lbs @ 28 mm	74 lbs @ 22 mm 107 lbs @ 22 mm	6 mm 6 mm	19.75 mm 19.95 mm

EVS Specifications



	P/N Each	Outer O.D. mm inch	Inner I.D. mm inch	L1 mm inch	F1 N LBS	L2 mm inch	Max. Lift mm inch	F2 N LBS	Lc mm inch	
	20456.01	16.4 0.65	11.4 0.45	28.0 1.10	150 34	22.0 0.87	6.0 0.24	330 74	19.8 0.78	
	20458.01	19.0 0.75	13.0 0.51	28.0 1.10	176 40	22.0 0.87	6.0 0.24	477 107	20.0 0.79	
	20439.01	20.5 0.81	15.5 0.61	32.0 1.26	98 22	18.0 0.71	14.0 0.55	310 70	15.0 0.59	
	20436.01	20.5 0.81	15.5 0.61	32.0 1.26	98 22	18.0 0.71	14.0 0.55	310 70	15.0 0.59	
	20409.01	22.2 0.87	16.2 0.64	33.4 1.31	175 39	22.4 0.88	11.0 0.43	433 97	20.6 0.81	
	20407.01	22.5 0.89	15.7 0.62	39.4 1.55	212 48	26.9 1.06	12.5 0.49	655 147	25.0 0.98	
	25100.01	24.3 0.96	17.1 0.67	37.5 1.48	232 52	26.0 1.02	11.5 0.45	647 145	24.5 0.96	
	20452.01	24.8 0.98	17.6 0.69	38.0 1.50	289 65	24.5 0.96	13.5 0.53	775 174	22.9 0.90	
	20442.02	25.2 0.99	14.0 0.55	35.0 1.38	260 58	21.0 0.83	14.0 0.55	750 169	19.9 0.78	
	TRD9B5.02	25.3 0.99	13.3 0.52	33.2 1.30	316 71	22.4 0.88	10.8 0.42	870 196	21.2 0.83	
	20405.02	25.5 1.01	13.6 0.54	34.2 1.35	337 76	21.2 0.83	13.0 0.51	999 224	19.9 0.78	
	20410.01	25.6 1.01	18.0 0.71	39.0 1.54	292 66	27.0 1.06	12.0 0.47	886 199	24.2 0.95	
	20441.01	25.6 1.01	18.2 0.72	34.0 1.34	250 56	23.0 0.91	11.0 0.43	740 166	21.1 0.83	
	20468.02	25.6 1.01	13.6 0.54	34.0 1.34	280 63	21.5 0.85	12.5 0.49	1,245 280	19.9 0.78	
	22632.02	26.0 1.02	14.4 0.57	34.8 1.37	256 58	20.8 0.82	14.0 0.55	750 169	19.5 0.77	
	20463.01	26.0 1.02	17.6 0.69	43.0 1.69	348 78	33.0 1.30	11.0 0.43	944 212	30.7 1.21	
	25409.01	26.4 1.04	18.8 0.74	39.9 1.57	375 84	25.9 1.02	14.0 0.55	897 202	24.1 0.95	
	25430.01	26.5 1.04	19.1 0.75	38.1 1.50	381 86	26.1 1.03	12.0 0.47	902 203	24.3 0.96	
	20432.02	26.6 1.05	14.2 0.56	35.8 1.41	356 80	24.1 0.95	11.7 0.46	935 210	22.1 0.87	
	25407.01	26.6 1.05	19.8 0.78	35.0 1.38	208 47	23.5 0.93	11.5 0.45	622 140	21.6 0.85	
	20457.01	26.7 1.05	19.1 0.75	36.0 1.42	275 62	25.0 0.98	11.0 0.43	780 175	23.2 0.91	
	25414.01	27.0 1.06	19.0 0.75	36.0 1.42	339 76	24.0 0.94	12.0 0.47	993 223	21.2 0.83	
	20445.01	27.0 1.06	19.0 0.75	41.9 1.65	359 81	29.9 1.18	12.0 0.47	940 211	28.4 1.12	
	20455.02	27.1 1.07	14.7 0.58	40.0 1.57	309 69	29.0 1.14	11.0 0.43	887 199	24.7 0.97	
	20438.01	27.5 1.08	20.1 0.79	32.0 1.26	265 60	20.0 0.79	12.0 0.47	765 172	18.5 0.73	
	20443.02	28.0 1.10	15.6 0.61	36.5 1.44	265 60	22.5 0.89	14.0 0.55	890 200	19.6 0.77	
	20440.02	28.5 1.12	15.8 0.62	40.0 1.57	367 82	26.0 1.02	14.0 0.55	1,059 238	24.3 0.96	
	25001.01	28.6 1.13	21.4 0.84	38.0 1.50	260 58	27.0 1.06	11.0 0.43	618 139	24.6 0.97	
	20430.02	29.0 1.14	21.5 0.85	34.8 1.37	394 89	20.7 0.81	14.1 0.56	1,207 271	19.8 0.78	
	20437.02	29.2 1.15	16.6 0.65	38.0 1.50	296 67	24.0 0.94	14.0 0.55	1,016 228	22.4 0.88	
	20466.01	29.2 1.15	21.0 0.83	39.0 1.53	365 82	27.5 1.08	11.5 0.45	963 216	25.4 1.00	
	20401.02	29.3 1.15	16.8 0.66	33.4 1.31	348 78	21.4 0.84	12.0 0.47	943 212	18.8 0.74	
	20402.02	29.3 1.15	16.8 0.66	36.4 1.43	356 80	23.4 0.92	13.0 0.51	1,004 226	21.9 0.86	
	20408.02	29.3 1.15	17.4 0.69	32.2 1.27	316 71	21.7 0.85	10.5 0.41	720 162	18.1 0.71	
	20411.02	29.4 1.16	16.9 0.67	40.5 1.59	367 82	27.0 1.06	13.5 0.53	1,060 238	25.3 1.00	
	20451.01	29.4 1.16	21.2 0.83	40.5 1.59	295 66	26.5 1.04	14.0 0.55	900 202	24.7 0.97	
	20460.02	29.4 1.16	16.6 0.65	36.4 1.43	358 80	23.4 0.92	13.0 0.51	1,055 237	21.6 0.85	
	20453.02	29.6 1.17	17.0 0.67	32.5 1.28	311 70	18.1 0.71	14.4 0.57	1,010 227	16.8 0.66	
	20454.02	29.6 1.17	16.8 0.66	40.0 1.57	309 69	29.0 1.14	11.0 0.43	898 202	23.8 0.94	
	25435.01	30.0 1.18	16.0 0.63	37.0 1.46	350 79	26.5 1.04	10.5 0.41	745 168	24.8 0.97	
	20406.02	30.2 1.19	17.9 0.70	31.8 1.25	329 74	20.3 0.80	11.5 0.45	840 189	16.1 0.63	
	20449.01	30.2 1.19	22.6 0.89	36.4 1.43	245 55	23.4 0.92	13.0 0.51	730 164	21.9 0.86	
	20448.01	30.5 1.20	22.5 0.89	36.5 1.44	300 67	21.5 0.85	15.0 0.59	945 212	20.0 0.79	
	20447.02	30.8 1.21	17.3 0.68	31.2 1.23	401 90	18.9 0.74	12.3 0.48	1,175 264	16.9 0.67	
	20415.01	31.2 1.23	22.2 0.87	43.2 1.70	409 92	31.8 1.25	11.4 0.45	950 213	27.5 1.08	
	20701.02	31.6 1.24	18.1 0.71	36.5 1.44	244 55	25.5 1.00	11.0 0.43	882 198	20.6 0.81	
	25408.01	31.6 1.24	22.6 0.89	45.7 1.80	600 135	30.5 1.20	14.2 0.56	1,282 288	28.2 1.11	
	20444.02	31.8 1.25	17.3 0.68	36.0 1.42	399 90	23.3 0.92	12.7 0.50	1,231 277	20.7 0.81	
	30011.01	31.8 1.25	21.8 0.86	43.2 1.70	490 110	31.8 1.25	13.5 0.53	1,291 290	29.5 1.16	
	30002.02	31.9 1.25	17.7 0.70	37.0 1.46	549 123	24.0 0.94	13.0 0.51	1,297 291	21.1 0.83	
	20450.02	32.0 1.26	18.0 0.71	39.2 1.54	339 76	24.2 0.95	15.0 0.59	1,090 245	21.0 0.83	
	20464.02	32.2 1.19	17.0 0.67	31.4 1.24	317 72	21.0 0.83	10.4 0.41	982 221	20.1 0.79	
	25410.01	32.3 1.27	22.3 0.88	45.7 1.80	740 166	31.6 1.25	14.1 0.55	1,730 389	30.0 1.18	
	20420.01	34.7 1.37	25.7 1.01	43.2 1.70	449 101	30.5 1.20	12.7 0.50	930 209	24.8 0.98	
	20427.01	35.0 1.38	26.0 1.02	47.3 1.86	560 126	35.6 1.40	11.7 0.46	933 210	27.5 1.08	
	20425.01	36.0 1.42	26.0 1.02	41.9 1.65	458 103	30.5 1.20	11.4 0.45	1,073 241	27.3 1.07	
	30006.02	36.1 1.42	20.6 0.81	45.7 1.80	538 121	27.9 1.10	17.8 0.70	1,611 362	25.1 0.99	
	30003.02	38.1 1.50	19.8 0.78	48.3 1.90	1,019 229	31.8 1.25	16.5 0.65	2,434 547	28.4 1.12	
	20422.01	38.3 1.50	27.6 1.08	47.8 1.88	600 135	34.3 1.35	13.5 0.53	1,277 287	31.5 1.24	
	30008.02	38.6 1.52	20.3 0.80	52.1 2.05	846 190	31.8 1.25	20.3 0.80	2,599 584	29.7 1.17	
	30007.01	39.1 1.54	28.4 1.12	48.3 1.90	645 145	34.3 1.35	14.0 0.55	1,469 330	31.5 1.24	
	30001.02	39.9 1.57	21.3 0.84	52.1 2.05	903 203	33.0 1.30	19.1 0.75	2,577 579	27.2 1.07	
	30013.02	39.9 1.57	20.8 0.82	52.1 2.05	832 187	35.6 1.40	16.5 0.65	2,430 546	31.8 1.25	
	30004.02	40.1 1.58	21.3 0.84	49.5 1.95	1,081 243	30.5 1.20	19.1 0.75	2,790 627	27.4 1.08	
	30010.02	40.4 1.59	21.3 0.84	52.1 2.05	979 220	31.8 1.25	20.3 0.80	3,168 712	29.7 1.17	
	35003.02	41.1 1.62	18.8 0.74	53.8 2.12	1,095 246	33.8 1.33	19.1 0.75	3,177 714	29.2 1.15	
	30005.02	41.3 1.63	21.6 0.85	50.8 2.00	1,135 255	31.8 1.25	19.1 0.75	3,075 691	28.7 1.13	
	30012.02	41.3 1.63	21.3 0.84	50.8 2.00	1,202 270	31.8 1.25	19.1 0.75	3,382 760	29.5 1.16	
	15001.01	41.9 1.65	27.2 1.07	52.1 2.05	676 152	33.0 1.30	19.1 0.75	1,744 392	29.7 1.17	
	30020.02	42.3 1.66	22.2 0.88	54.6 2.15	1,354 305	33.0 1.30	21.6 0.85	3,658 822	29.5 1.16	
	30021.03	42.3 1.66	15.9 0.63	52.6 2.07	1,634 367	32.3 1.27	20.3 0.80	4,304 967	30.2 1.19	

Fax 1-951-256-8333

**For the latest Information or Applications
Call 1-800-222-8811 8am-4pm PST
or visit eibach.com**

EVS-Pro



Ultra High Performance Valve Springs

Your Eibach Partner

USA

Eibach Springs, Inc.
264 Mariah Circle
Corona, CA 92879
☎ (1) 951 256-8300
☎ (1) 951 256-8333
✉ eibach@eibach.com

Germany

Heinrich Eibach GmbH
Am Lennedamm 1
57413 Finnentrop
☎ 49 (0) 2721 / 511-0
☎ 49 (0) 2721 / 511-111
✉ eibach@eibach.de

England

Eibach UK
Unit 25, Swannington Rd.
Broughton Astley
LE9 6TU Leicestershire
☎ 44 (0) 1455-286524
☎ 44 (0) 1455-285853
✉ sales@eibach.co.uk

Japan

Eibach Japan Co., Ltd.
3-9-36, Yuigahama
Kamakura-city
Kanagawa, 248-0014
☎ 81 (0) 467-61-3610
☎ 81 (0) 467-61-3615
✉ eibach@eibach.jp

Australia

Eibach Suspension Technology P.T.Y. Ltd.
3-4 Prosperity Parade
Warriewood 2102 NSW
☎ 61 (0) 2-9999-3655
☎ 61 (0) 2-9999-3855
✉ eibach@eibach.com.au

South Africa

Eibach South Africa P.T.Y. Ltd.
P.O. Box 2495
North End 6056, South Africa
☎ 27 (0) 41 451 5311
☎ 27 (0) 41 451 0196
✉ eibachsa@telkomsa.net

EVS-17-NA



The Suspension Company.